

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/051482 A3

(51) International Patent Classification⁷: **G06F 12/14**, 1/00

(21) International Application Number:
PCT/IB2003/005271

(22) International Filing Date:
19 November 2003 (19.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
102 56 587.2 4 December 2002 (04.12.2002) DE

(71) Applicant (for DE only): **PHILIPS INTELLECTUAL
PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).

(71) Applicant (for all designated States except DE, US):
KONINKLIJKE PHILIPS ELECTRONICS N.V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FEUSER, Markus**

[DE/DE]; c/o Philips Intellectual Property & Standards
GmbH, Weissshausstr. 2, 52066 Aachen (DE). **SOMMER,
Sabine** [DE/DE]; c/o Philips Intellectual Property &
Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).


(74) Agent: **MEYER, Michael**; Philips Intellectual Property &
Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ADDRESS ENCRYPTION METHOD FOR FLASH MEMORIES



(57) Abstract: In order to further develop a data processing device, in particular an electronic memory component, comprising a plurality of access-secured sub-areas, in particular a plurality of access-secured memory areas, each having at least one assigned parameter ($a_n, a_{n-1}, \dots, a_1, a_0$), in particular address, and a method of encrypting at least one parameter ($a_n, a_{n-1}, \dots, a_1, a_0$), in particular the address, of at least one access-secured sub-area, in particular at least one access-secured memory area, of at least one data processing device, in particular at least one electronic memory component, in such a way that on the one hand the security of such devices is increased considerably and on the other hand the associated expense and technical complexity are not too great, it is proposed that the parameter ($a_n, a_{n-1}, \dots, a_1, a_0$) of at least one sub-area be capable of encryption only in certain areas, i.e. in dependence on at least one further sub-area ($a'_n, a'_{n-1}, \dots, a'_1, a'_0$).

WO 2004/051482 A3